

SPRAYCANNONS

WE BEAT ODOUR AND DUST!



BIG
WORK TOOLS

SPRAYCANNONS

LEGENDA

STAND ALONE SERIESP 2 - P14

MAST SERIESP15 - P20

SKID MOUNTED-SERIES.....P21 - P24

SELF SUPPORTING SERIES.....P25 - P31

WALL MOUNTED SERIES.....P32 - P34

STAND-ALONE SERIES SPRAYCANNON 5



www.bigworktools.nl



Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Indoor
Distance (m)	5-10 (windstill cond.)
Surface (m ²)	6,5
Quantity of Nozzles	3
Water Usage (l/h)	0-19
Vertical Angle (°)	0-60
Oscillation Angle (°)	No
Electricity	110V/230V
Supply Connection	1"
Supply Pressure (Bar)	1
Dimensions LxBxH (mm.)	30x20x40
Weight (kg.)	4,5

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



STAND-ALONE SERIES SPRAYCANNON 15



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Indoor/Outdoor
Distance (m)	10-20 (windstill cond.)
Surface (m ²)	40
Quantity of Nozzles	9
Water Usage (l/h)	1-200
Fan (kW)	0,28
Pump (kW)	No
Working Pressure (Bar)	-
Vertical Angle (°)	0-90
Oscillation Angle (°)	No
Electricity	110V/230V
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	550x440x730
Weight (kg.)	18

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



STANDARD EQUIPPED WITH

- ✓ Fan Speed regulation
- ✓ Water Flow regulation

STAND-ALONE SERIES SPRAYCANNON 25



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Indoor/Outdoor
Distance (m)	15-25 (windstill cond.)
Surface (m ²)	70
Quantity of Nozzles	12
Nozzle Ring	Stainless Steel
Water Usage (l/h)	1-300
Fan (kW)	1,5
Pump (kW)	0,75
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	No
Electricity	110/230V
Socket	16A
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1600x780x1000
Weight (kg.)	100



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



STAND-ALONE SERIES SPRAYCANNON 35



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	20-35 (windstill cond.)
Surface (m ²)	3400
Quantity of Nozzles	16
Water Usage (l/h)	1-1000
Fan (kW)	2,2
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	110/230V
Socket	16A
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1300x900x1300
Weight (kg.)	230

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

STAND-ALONE SERIES SPRAYCANNON 40



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Indoor/Outdoor
Distance (m)	25-40 (windstill cond.)
Surface (m ²)	4400
Quantity of Nozzles	16
Water Usage (l/h)	1-1000
Fan (kW)	3
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	16A
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1300x900x1300
Weight (kg.)	240



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

STAND-ALONE SERIES SPRAYCANNON 50



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	30-50 (windstill cond.)
Surface (m ²)	7.000
Quantity of Nozzles	26
Water Usage (l/h)	500-3.500
Fan (kW)	5,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	32A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1850x1400x2050
Weight (kg.)	500

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

STAND-ALONE SERIES SPRAYCANNON 60



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	40-60 (windstill cond.)
Surface (m ²)	10.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Fan (kW)	7,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	32A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1850x1400x2200
Weight (kg.)	615

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

STAND-ALONE SERIES SPRAYCANNON 75



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	50-75 (windstill cond.)
Surface (m ²)	15.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Fan (kW)	18,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	63A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1850x1400x2200
Weight (kg.)	650

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

STAND-ALONE SERIES SPRAYCANNON 90



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	60-90 (windstill cond.)
Surface (m ²)	22.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Fan (kW)	18,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	63A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1850x1400x2300
Weight (kg.)	700



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

STAND-ALONE SERIES SPRAYCANNON 100



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	70-100 (windstill cond.)
Surface (m ²)	27.500
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500/9.000
Fan (kW)	22
Pump (kW)	4/5,5/7,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	63A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1850x1400x2300
Weight (kg.)	750

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator
- ✓ Self-Supporting including water bowser and generator

STAND-ALONE SERIES SPRAYCANNON 130



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	110-130 (windstill cond.)
Surface (m ²)	48.000
Quantity of Nozzles	68
Water Usage (l/h)	500-15.000
Fan (kW)	30
Pump (kW)	11
Working Pressure (Bar)	20-25
Vertical Angle (°)	0 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	125A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	2500x2000x2570
Weight (kg.)	1100



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

STAND-ALONE SERIES SPRAYCANNON 150



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	120-150 (windstill cond.)
Surface (m ²)	60.000
Quantity of Nozzles	68
Water Usage (l/h)	500-15.000
Fan (kW)	45
Pump (kW)	11
Working Pressure (Bar)	20-25
Vertical Angle (°)	0 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	125A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	2500x2000x2570
Weight (kg.)	1200



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV-installation
- ✓ Wheel Set
- ✓ Skid-mounted including generator

MAST SERIES SPRAYCANNON 40-M



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Indoor and Outdoor
Distance (m)	40 (windstill cond.)
Surface (m²)	4400
Quantity of Nozzles	16
Mast (Hydraulic/SS)	4 m. high
Water Usage (l/h)	1-1000
Fan (kW)	3
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	16A
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	1300x900x2500 (folded)
Unfolded Mast Height (mm.)	4000
Weight (kg.)	350

AVAILABLE OPTIONS

✓ Electrical Oscillation
✓ Fan Speed regulation
✓ Water Flow regulation
✓ Remote Control
✓ UV installation
✓ Trailer



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

MAST SERIES SPRAYCANNON 50/60BM



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	40-60 (windstill cond.)
Surface (m ²)	10.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Fan (kW)	5,5/7,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	32A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	2430x1910x2720 (folded)
Unfolded Mast Height (mm.)	5750
Weight (kg.)	915

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control

MAST SERIES SPRAYCANNON 90-BM



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	60-90 (windstill cond.)
Surface (m ²)	22.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500/6.500
Fan (kW)	18,5
Pump (kW)	4/5,5/7,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	63A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	2430x1910x2720 (folded)
Unfolded Mast Height (mm.)	5750
Weight (kg.)	915

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control

MAST SERIES SPRAYCANNON 100-BM



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	70-100 (windstill cond.)
Surface (m ²)	27.500
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500/6.500
Fan (kW)	22
Pump (kW)	4/5,5/7,5
Working Pressure (Bar)	15-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Electricity	400V
Socket	63A
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	2430x1910x2820 (folded)
Unfolded Mast Height (mm.)	5850
Weight (kg.)	1015

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control

MAST SERIES SPRAYCANNON 50/60-SBM



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	40-60 (windstill cond.)
Surface (m ²)	10.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Fan (kW)	5,5/7,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator	20 kVA
Skid Dimensions (mm.)	3000x1950x200
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	3000x2500x2920 (folded)
Unfolded Mast Height (mm.)	5950
Weight (kg.)	2000

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control

MAST SERIES SPRAYCANNON 50/60-SMT



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	40-60 (windstill cond.)
Surface (m²)	10.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Fan (kW)	5,5/7,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator	30 kVA
Rubber tracks	Included
Supply Connection	2"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	4000x2100x3050 (folded)
Unfolded Mast Height (mm.)	6110
Weight (kg.)	3200



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control



SKID-MOUNTED SERIES SPRAYCANNON 40-SKID



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	25-40 (windstill cond.)
Surface (m ²)	4.400
Quantity of Nozzles	16
Water Usage (l/h)	1.000
Fan (kW)	3,0
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	8 (Diesel)
Weight (kg)	739kg
Dimensions LxBxH (mm.)	1750x1250x1415



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

SKID-MOUNTED SERIES SPRAYCANNON 50-SKID



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	30-50 (windstill cond.)
Surface (m ²)	7.000
Quantity of Nozzles	26
Water Usage (l/h)	500-3.500
Fan (kW)	5,5
Pump (kW)	4
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	20 (Diesel)
Weight (kg)	1.550kg
Dimensions LxBxH (mm.)	3000x2000x2200



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

SKID-MOUNTED SERIES SPRAYCANNON 60-SKID



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	40-60 (windstill cond.)
Surface (m ²)	10.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500
Fan (kW)	7,5
Pump (kW)	4
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	20 (Diesel)
Weight (kg)	1.600kg
Dimensions LxBxH (mm.)	3000x2000x2400



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

SKID-MOUNTED SERIES SPRAYCANNON 90-SKID



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	60-90 (windstill cond.)
Surface (m ²)	22.000
Quantity of Nozzles	34
Water Usage (l/h)	500 – 4.500
Fan (kW)	18,5
Pump (kW)	5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	40 (Diesel)
Weight (kg)	2.060kg
Dimensions LxBxH (mm.)	3000x2000x2500



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

SELF-SUPPORTING SERIES SPRAYCANNON 25-SS



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	15-25 (windstill cond.)
Surface (m ²)	70
Quantity of Nozzles	12
Water Usage (l/h)	1-300
Water Bowser (l)	1150
Fan (kW)	1,5
Pump (kW)	0,75
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Horizontal Angle (°)	359 (manually)
Generator (kVA)	4 (petrol)
Trailer	2 axled / public road
Dimensions LxBxH (mm.)	3200x1700x2000



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Fan Speed regulation
- ✓ Road Watering
- ✓ UV installation

SELF-SUPPORTING SERIES SPRAYCANNON 40-SS



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	25-40 (windstill cond.)
Surface (m²)	4400
Quantity of Nozzles	16
Water Usage (l/h)	1-1000
Water Bowser	2.000-5.000
Fan (kW)	3
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	8 (Diesel)
Skid	Powder Coated Steel
Dimensions LxBxH (mm.)	3500x1350x1500



APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.

AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Trailer

SELF-SUPPORTING SERIES SPRAYCANNON 40-SS-M



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	25-40 (windstill cond.)
Surface (m ²)	4400
Quantity of Nozzles	16
Mast (Hydraulic/SS)	4 m. high
Water Usage (l/h)	1-1000
Water Bowser	2.000-5.000
Fan (kW)	3
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	8 (Diesel)
Skid	Powder Coated Steel
Dimensions LxBxH (mm.)	3500x1350x2500

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Fan Speed regulation
- ✓ Water Flow regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Trailer

SELF-SUPPORTING SERIES SPRAYCANNON 50-SS



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	30-50 (windstill cond.)
Surface (m ²)	7.000
Quantity of Nozzles	26
Water Usage (l/h)	500-3.500
Water Bowser (l)	2.000
Fan (kW)	5,5
Pump (kW)	4
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	20 (Diesel)
Skid	Powder Coated Steel
Dimensions LxBxH (mm.)	3000x1860x2680

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

SELF-SUPPORTING SERIES SPRAYCANNON 60-SS



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	40-60 (windstill cond.)
Surface (m²)	10.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500
Water Bowser (l)	2.000
Fan (kW)	7,5
Pump (kW)	4
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	20 (Diesel)
Skid	Powder Coated Steel
Dimensions LxBxH (mm.)	3000x1860x2850

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

SELF-SUPPORTING SERIES SPRAYCANNON 75-SS



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	60-75 (windstill cond.)
Surface (m ²)	16.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Water Bowser (l)	2.000
Fan (kW)	11
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	20 (Diesel)
Dimensions LxBxH (mm.)	3220x1861x2842

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

SELF-SUPPORTING SERIES SPRAYCANNON 90-SS



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	60-90 (windstill cond.)
Surface (m²)	22.000
Quantity of Nozzles	34
Water Usage (l/h)	500-3.500/4.500
Water Bowser (l)	2.000
Fan (kW)	18,5
Pump (kW)	4/5,5
Working Pressure (Bar)	20-25
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	40 (Diesel)
Skid	Powder Coated Steel
Dimensions LxBxH (mm.)	3000x2000x2880

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

WALL-MOUNTED SERIES SPRAYCANNON 15-W



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHN. SPECIFICATIONS SPRAYCANNON

Usage	Indoor/Outdoor
Distance (m)	10-20 (windstill cond.)
Surface (m²)	630
Quantity of Nozzles	9
Water Usage (l/h)	1-200
Fan (kW)	0,28
Pump (kW)	0,75
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-180
Supply Pressure (Bar)	1-9
Dimensions LxWxH (mm.)	1135x600x1450

TECHNICAL CONTROL BOX

Usage	Indoor/Outdoor
Electrical Area	Electrical cabinet
Water Area	Pump/Motor, filters, valves
Dimensions LxWxH (mm)	935x651x927
Electricity	400V/16A/5P
Socket	16A



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed/Water Flow regulations
- ✓ Remote Control
- ✓ Water Softener
- ✓ UV installation

APPLICATION AREAS

RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS ETC.

WALL-MOUNTED SERIES SPRAYCANNON 25-W



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHN. SPECIFICATIONS SPRAYCANNON

Usage	Indoor/Outdoor
Distance (m)	15-25 (windstill cond.)
Surface (m²)	980
Quantity of Nozzles	12
Water Usage (l/h)	1-300
Fan (kW)	1,5
Pump (kW)	0,75
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-180
Supply Pressure (Bar)	1-9
Dimensions LxWxH (mm.)	1380x580x1450



TECHNICAL CONTROL BOX

Usage	Indoor/Outdoor
Electrical Area	Electrical cabinet
Water Area	Pump/Motor, filters, valves
Dimensions LxWxH (mm)	935x651x927
Electricity	400V/16A/5P
Socket	16A



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed/Water Flow regulations
- ✓ Remote Control
- ✓ Water Softener
- ✓ UV installation

APPLICATION AREAS

RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS ETC.

WALL-MOUNTED SERIES SPRAYCANNON 40-W



www.bigworktools.nl

Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

TECHN. SPECIFICATIONS SPRAYCANNON

Usage	Indoor/Outdoor
Distance (m)	25-40 (windstill cond.)
Surface (m²)	4400
Quantity of Nozzles	16
Water Usage (l/h)	1-1000
Fan (kW)	3
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-180
Supply Pressure (Bar)	1-9
Dimensions LxWxH (mm.)	1650x670x1520



TECHNICAL CONTROL BOX

Usage	Indoor/Outdoor
Electrical Area	Electrical cabinet
Water Area	Pump/Motor, filters, valves
Dimensions LxWxH (mm)	935x651x927
Electricity	400V/16A/5P
Socket	16A



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed/Water Flow regulations
- ✓ Remote Control
- ✓ Water Softener
- ✓ UV installation

APPLICATION AREAS

RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS ETC.



Office address: Schiemerik 1 | 5334 NL Velddriel | The Netherlands
Office: +31418 67 45 45 | Mobile / WhatsApp: +31 6 38 22 82 89

www.bigworktools.nl